TECHNICAL DATA SHEET

Cosmedico®
FIRST CHOICE IN TANNING

COSMOFIT+ R 19 120W 2.0M

NAFTA Code: FR79 T12 120W PH
Equivalency Code: 120-R-19/1,9

Item Code: 16718

Electrical data (nominal values)	
Lamp power	120 W
Supply voltage	230 V
Ballast	120 W / 230 V

Physical data	
UVA flux (315-400 nm) ±10%	38 W
UVA irradiance (315-400 nm) ±10%	23 W/m²
UVB irradiance (280-315 nm) ±10%	79 mW/m²
UVB/UVA ratio	0,4 %
Recommended useful life	800 hrs

Lamp specifications (acc. IEC/EN 61228)

a) Dimensions (in mm)	
Length (nominal)	2.000,0
Length without pins (max)	2.001,3
Length base – pin (min)	2.006,0
Length base – pin (max)	2.008,4
Length with pins (max)	2.015,5
Diameter (nominal/max)	38,0 / 40,5
Base	G13 standard

b) Reflector	210°

c) Specified ballast	Cosmopower 74201 120W 1,2A 230V

d) Electrical data (rated values)	
Lamp power	114 W
Lamp current	1.090 mA
Lamp voltage	124 V

e) Effective irradiance (rated values)	
UV-Erythema (250-400 nm) ±15%	19 mW/m²
nmsc (250-320 mm) ±15%	18 mW/m²
nmsc (320-400 mm) ±15%	9 mW/m²

f) Equivalency code	120-R-19/1,9

Examples of exposure times

UVA irradiance	First session tanning time	Maximum tanning time in Min. by skin type		
in W/m²	*in Min.*	*2*	*3*	*4*
180	10,2	25,4	35,5	45,7
230	7,9	19,9	27,8	35,8
280	6,5	16,3	22,9	29,4
330	5,5	13,9	19,4	24,9
380	4,8	12,0	16,8	21,7

(depending on the actual UVA irradiance of the sunbed)

Construction elements	
Mount	SM
Glass type	open
Light Colour	see picture

Equipment requirements	
Starter	120 W / 230 V

Additional specifications

This lamp is intended for sun-tanning purposes only and shall not be used in any other application

Relative spectral distribution